

RG Typen RG types

RG



Anwendung

In der Hochfrequenz-Übertragungstechnik, speziell in Sender- und Empfangsanlagen, Computerbranche, Industrie- und Unterhaltungselektronik. Aufgrund ihrer unterschiedlichen elektronischen, thermischen und mechanischen Möglichkeiten je nach Kabeltyp bis in den Gigahertzbereich einsetzbar.

Approbationen/Normen

US-Militärspezifikation MIL-C-17

Aufbau

Innenleiter	1 x 0,6 Staku-blank
Aderisolierung	3,7 PE
Gesamtschirmung	Geflecht Cu, blank
Außenmantelmaterial	Spezial Polyvinylchlorid (PVC)/HM2

Technische Daten

Isolationswiderstand	10 ⁵ MOhm/km
Betriebskapazität	67 pF/m
Schleifenwiderstand	171 Ohm/km
Wellenwiderstand:	75±3 Ohm
Dämpfung ca. dB/100 m:	
200 MHz:	16,5
400 MHz:	24
800 MHz:	35
Biegeradius fest (xD)	12
Betriebstemp. fest	-35°C ... +80°C

application

Used in high frequency transmission, especially for transmitters and receivers, computers, radio and TV transmissions. The varied mechanical, thermal and electronic properties of coaxial cables allow the use to GHz levels according to the cable type.

approvals/standards

US-Military specifications MIL-C-17

structure

inner conductor	1 x 0,6 Steel/copper, bare
core insulation	3,7 PE
overall shield	bare, copper braid
outer sheath material	special polyvinylchlorid (PVC)/HM2

specifications

insulation resistance	10 ⁵ MOhm/km
operating capacity	67 pF/m
conductor loop resistance	171 Ohm/km
Impedance:	75±3 Ohm
Attenuation approx. dB/100 m:	
200 MHz:	16,5
400 MHz:	24
800 MHz:	35
bending radius fixed	12
operation temp. fixed	-35°C ... +80°C

Art. nr. art. no.	Typ type	Abmessung dimensions [n x mm2]	Farbe colour	Außen-Ø outer-Ø [mm]	Gewicht weight [kg]
03001004	PVC	RG 59 B/U	schwarz black	6,2	52
03001024	LSOH	RG 59 B/U	schwarz black	6,2	52